

Product Code: CMA052

Technical Specification











General Information

Plate Dimensions (mm) 86 (W) x 86 (H) x 9.5 (D)

Plate Fixing Centres - Horizontal (mm) 603

> Style Rounded Profile Polar White Colour

Front Plate, Rocker Switch & Fuse Drawer: Materials Rear Housing: Urea

Neon Lens: Polycarbonate Terminals: Brass

Contacts: Silver "on-lay" Copper / Brass Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel

Anti Microbial Certified

Operating Voltage (AC) 250 Frequency (Hz) 50

Resistive Load Rating (A)

Fuse Fitted Type Plug Top Cartridge Fuse

Termination Type

Terminal Size (mm) Terminal Torque Value (Nm) 2

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

> Switched Yes Double Pole Switch Twin Earth Terminals Yes

> > Neon Indicator Yes Indicator Colour Orange

Product Marking Fused Flex Outlet Available Yes

Flex Outlet Dimension (mm) Flex Outlet Location Bottom of Plate

Minimum Back Box Depth (mm)

Ingress Protection IP20 Operational Temperature (°C) -5 to +40 Warranty (Years)

Standards BS 1363-4, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom











Specification is subject to change without notice. Errors & Omissions excluded.