


Product Code: CMA1032AG

Luckinslive 438093964



General Information

| | | |
|--|--|--|
| Plate Dimensions (mm) | 146 (W) x 86 (H) x 9.5 (D) | |
| Plate Fixing Centres - Horizontal (mm) | 120.6 | |
| Style | Rounded Profile | |
| Colour | Anthracite Grey | |
| Materials | Front Plate: Urea Terminals: Brass Earth Strap: Mild Steel | Rear Housing: Urea Terminal Screws: Steel & Yellow Passivated |
| Anti Microbial Certified | Yes | |
| Operating Voltage (AC) | 250 | Frequency (Hz) 50 |
| Resistive Load Rating (A) | 13 | |
| Termination Type | Screw | |
| Terminal Size (mm) | Ø5 | Terminal Torque Value (Nm) 2 |
| Terminal Capacity - Solid (mm ²) | 3 x 2.5 or 2 x 4 | |
| Double Pole Switch | No | |
| 3 Pin Safety Shuttered | Yes | |
| Twin Earth Terminals | Yes | |
| Minimum Back Box Depth (mm) | 25 | |
| Ingress Protection | IP20 | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 25 | |

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All grey moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.



CLICK OR SCAN



Catalogue



Range



DoC



Installation