

Product Code: CMA2652-OV

Luckinslive 438961805

Description: 13A Double Pole Switched Lockable Fused Connection Unit With LED - Fused, Oven



General Information

|                                        |                                                |                                            |
|----------------------------------------|------------------------------------------------|--------------------------------------------|
| Plate Dimensions (mm)                  | 86 (W) x 86 (H) x 9.5 (D)                      |                                            |
| Plate Fixing Centres - Horizontal (mm) | 60.3                                           |                                            |
| Style                                  | Rounded Profile                                |                                            |
| Colour                                 | Polar White                                    |                                            |
| Materials                              | Front Plate, Rocker Switch & Fuse Drawer: Urea | Rear Housing: Urea                         |
|                                        | Terminals: Brass                               | Terminal Screws: Steel & Yellow Passivated |
|                                        | Contacts: Silver "on-lay" Copper / Brass       | Internal Busbars: Formed Pressed Brass     |
|                                        | Earth Strap: Mild Steel                        |                                            |
| Anti Microbial Certified               | Yes                                            |                                            |
| Operating Voltage (AC)                 | 250                                            | Frequency (Hz) 50                          |
| Resistive Load Rating (A)              | 13                                             |                                            |
| Fuse Fitted Type                       | Plug Top Cartridge Fuse                        |                                            |
| Termination Type                       | Screw                                          |                                            |
| Terminal Size (mm)                     | Ø5                                             | Terminal Torque Value (Nm) 2               |
| Terminal Capacity - Solid (mm²)        | 3 x 2.5 or 2 x 4                               |                                            |
| Switched                               | Yes                                            |                                            |
| Double Pole Switch                     | Yes                                            |                                            |
| Twin Earth Terminals                   | Yes                                            |                                            |
| LED Indicator                          | Yes                                            | Indicator Colour Red                       |
| Product Marking                        | Fused, Oven                                    |                                            |
| Minimum Back Box Depth (mm)            | 25                                             |                                            |
| Ingress Protection                     | IP20                                           |                                            |
| Operational Temperature (°C)           | -5 to +40                                      |                                            |
| Warranty (Years)                       | 25                                             |                                            |

Standards BS 1363-4, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

LED Indicators are not designed to withstand insulation resistance testing at 500V. Carrying out insulation resistance testing at 500V may result in damage to the LED indicator. Please disconnect prior to insulation resistance testing.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

