

Product Code: CMA30651

Luckinslive 433613019

Description: 13A Zigbee Smart Switched Fused Connection Unit



General Information

Range	MODE®	
Dimensions With Gasket (mm)	86 (W) x 86 (H) x 20.5 (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Style	Rounded Profile	
Gasket Colour	Polar White	
Materials	Front Plate: Urea Terminals: Brass Internal Busbars: Formed Pressed Brass Gasket: Polycarbonate	Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Electronics: PCB & Electronic Components
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Fuse Type	Plug Top Cartridge Fuse	
Termination Type	Screw	
Terminal Size (mm)	5.7 x 4.8	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	
Single Pole Switched	Yes	
Twin Earth Terminals	No	
Protocol	Zigbee	Signal Transmission Frequency 2.4GHz
Open Air Wireless Range (M)	<160	
Standby Current (mA)	1	
Indicator Colour	White & Orange	
Minimum Back Box Depth (mm)	25 (With Gasket) 35 (Without Gasket)	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	3	

Standards BS 1363-4 & BS 1362, BS EN 61000-6-1, BS EN 61000-6-3, BS EN 60669-2-1 in conjunction with BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Zigbee signal mesh
 Enables manual control (unless locked), wireless control and automated control
 Voice control via ClickSmart+ Hub using Alexa and/or Google Home.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
 All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.
 All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Components Supplied Smart Fused Connection Unit, Gasket, Fixing Screws, Screw Caps, Instruction Manual

Programming Information With hub and app setup and socket wired and powered, press the switch for five to ten seconds, the orange LED indicator starts flashing. Can be paired with hub via app.

