

Product Code: CMA796

Description: 13A 2 Gang Switched Socket Outlet With Twin Type C USB (4.2A) Outlets



General Information

| | | |
|--|--|--|
| Plate Dimensions (mm) | 146 (W) x 86 (H) x 9.5 (D) | |
| Plate Fixing Centres - Horizontal (mm) | 120.6 | |
| Style | Rounded Profile | |
| Colour | Polar White | |
| Materials | Front Plate & Rocker Switch: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass PCB: Mixed Components | Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel |
| Anti Microbial Certified | Yes | |
| Operating Voltage (AC) | 250 | Frequency (Hz) 50 |
| Resistive Load Rating (A) | 13 | |
| USB Output Type | USB Type 'C' | |
| USB Number Of Outputs | 2 | USB Charging Total Load (A) 4.2 |
| USB Charging Voltage (V DC) | 5 | USB Standby Current (W) 0.1 |
| Termination Type | Screw | Terminal Torque Value (Nm) 1.2 |
| Terminal Size (mm) | Ø5 | |
| Terminal Capacity - Solid (mm ²) | 3 x 2.5 or 2 x 4 | |
| Single Pole Switched | Yes | |
| 3 Pin Safety Shuttered | Yes | |
| Twin Earth Terminals | Yes | |
| Product Marking | 5V DC 4.2A (SHARED) | |
| Minimum Back Box Depth (mm) | 25 | |
| Ingress Protection | IP20 | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 25 | Warranty - Electronics (Years) 2 |
| Standards | BS 1363-2: 2016 +A1: 2018, EN IEC 62368-1, EN IEC 62368-3, EN IEC 62680-1-3, EN IEC 61000-6-1 & EN 61000-6-3 | |

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

The USB circuits within this socket outlet are designed to withstand insulation resistance tests at 500V.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Independent Charging: 5V DC, 4.2A – USB Type C (3A), USB Type C (3A)

Intelligent chip incorporated within the USB PCB adjusts the output according to the load connected.