

Product Code: CPC034

Description: 15A Round Pin 1 Gang Switched Socket



General Information

Dimensions (mm)	86mm (W) x 86mm (H) x 32.5mm (D)	
Plate Dimensions (mm)	86mm (W) x 86mm (H) x 6.5mm (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Style	Screwless	
Colour	White	
Insert Colour	White	
Materials	Cover Plate: Polycarbonate	Insert, Switch & Base: Polycarbonate
	Terminals : Brass Plated Steel	Terminal Screws: Steel & Yellow Passivated
	Contacts : Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass
	Earth Strap : Mild Steel	
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	15	
Termination Type	Screw	
Terminal Size (mm)	Ø4	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 2 x 4	
Number Of Socket Outlets	1	
Switched	Yes	
Single Pole Switched	Yes	
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Standards BS 546

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

