

Product Code: CPC036

Description: 13A 2 Gang Double Pole Switched UK Socket



General Information

Dimensions (mm)	146 (W) x 86 (H) x 27.5 (D)		
Plate Dimensions (mm)	146 (W) x 86 (H) x 6.5 (D)		
Plate Fixing Centres - Horizontal (mm)	120.6		
Style	Screwless		
Colour	White		
Insert Colour	White		
Materials	Cover Plate: Polycarbonate	Insert, Switch & Base: Polycarbonate	
	Terminals: Brass Plated Steel	Terminal Screws: Steel & Yellow Passivated	
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass	
	Earth Strap: Mild Steel		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Termination Type	Screw		
Terminal Size (mm)	Ø4	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 2 x 4		
Number Of Socket Outlets	2		
Double Pole Switch	Yes		
Minimum Back Box Depth (mm)	35		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

