

Product Code: CPC050

Description: 13A Fused Connection Unit With Flex Outlet



General Information

Dimensions (mm)	86 (W) x 86 (H) x 23,5 (D)	
Plate Dimensions (mm)	86 (W) x 86 (H) x 6,5 (D)	
Plate Fixing Centres - Horizontal (mm)	60,3	
Style	Screwless	
Colour	White	
Insert Colour	White	
Materials	Cover Plate & Fuse Drawer: Polycarbonate	Insert & Base: Polycarbonate
	Terminals: Brass Plated Steel	Terminal Screws: Steel & Yellow Passivated
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Fuse Fitted Type	13A (BS 1362)	
Termination Type	Screw	
Terminal Size (mm)	Ø4	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm ²)	3 x 2,5 or 2 x 4	
Switched	No	
Product Marking	Fused	
Flex Outlet Available	Yes	
Flex Outlet Location	Yes (Through Front of the Plate)	Flex Outlet Dimension (mm) Ø10
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Standards BS 1363-4, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

CLICK OR SCAN	<p>Catalogue</p>	<p>Range</p>	<p>DoC</p>	<p>Installation</p>	CLICK OR SCAN
----------------------	------------------	--------------	------------	---------------------	----------------------