

Product Code: CPC052SV

Description: 13A Fused Connection Unit Double Pole Switched With Flex Outlet & Neon



**General Information**

Dimensions (mm)	86 (W) x 86 (H) x 23,5 (D)		
Plate Dimensions (mm)	86 (W) x 86 (H) x 6,5 (D)		
Plate Fixing Centres - Horizontal (mm)	60,3		
Style	Screwless		
Colour	Silver		
Insert Colour	Silver		
Materials	Cover Plate, Neon Lens & Fuse Drawer: Polycarbonate	Insert, Switch & Base: Polycarbonate	
	Terminals: Brass Plated Steel	Terminal Screws: Steel & Yellow Passivated	
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass	
	Earth Strap: Mild Steel		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Fuse Fitted Type	13A (BS 1362)		
Termination Type	Screw		
Terminal Size (mm)	Ø4	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm <sup>2</sup> )	3 x 2,5 or 2 x 4		
Switched	Yes		
Double Pole Switch	Yes		
Neon Indicator	Yes	Indicator Colour	Red
Product Marking	Fused		
Flex Outlet Available	Yes		
Flex Outlet Location	Yes (Through Front of the Plate)	Flex Outlet Dimension (mm)	Ø10
Minimum Back Box Depth (mm)	35		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		

**Standards** BS 1363-4, BS 1362

**Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

