

Product Code: CPC053BK
Description: 13A Fused Connection Unit With Flex Outlet & Neon



General Information

Dimensions (mm)	86mm (W) x 86mm (H) x 23.5mm (D)		
Plate Dimensions (mm)	86mm (W) x 86mm (H) x 6.5mm (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Screwless		
Colour	Black		
Insert Colour	Black		
Materials	Cover Plate, Neon Lens & Fuse Drawer: Polycarbonate		
	Terminals : Brass Plated Steel	Insert, Switch & Base: Polycarbonate	
	Internal Busbars: Formed Pressed Brass	Terminal Screws: Steel & Yellow Passivated	
		Earth Strap : Mild Steel	
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Fuse Fitted Type	Plug Top Cartridge Fuse		
Termination Type	Screw		
Terminal Size (mm)	Ø4	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4		
Switched	No		
Neon Indicator	Yes	Indicator Colour	Red
Product Marking	Fused		
Flex Outlet Available	Yes		
Flex Outlet Location	Through Front of the Plate	Flex Outlet Dimension (mm)	Ø10
Minimum Back Box Depth (mm)	35		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		

Standards BS 1363-4, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

