

Product Code: CPC053SV

Description: 13A Fused Connection Unit With Flex Outlet & Neon



General Information

Dimensions (mm)	86mm (W) x 86mm (H) x 23,5mm (D)	
Plate Dimensions (mm)	86mm (W) x 86mm (H) x 6,5mm (D)	
Plate Fixing Centres - Horizontal (mm)	60,3	
Style	Screwless	
Colour	Silver	
Insert Colour	Silver	
Materials	Cover Plate, Neon Lens & Fuse Drawer: Polycarbonate	Insert, Switch & Base: Polycarbonate
	Terminals : Brass Plated Steel	Terminal Screws: Steel & Yellow Passivated
	Internal Busbars: Formed Pressed Brass	Earth Strap : Mild Steel
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Fuse Fitted Type	Plug Top Cartridge Fuse	
Termination Type	Screw	
Terminal Size (mm)	Ø4	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm ²)	3 x 2,5 or 2 x 4	
Switched	No	
Neon Indicator	Yes	Indicator Colour Red
Product Marking	Fused	
Flex Outlet Available	Yes	
Flex Outlet Location	Through Front of the Plate	Flex Outlet Dimension (mm) Ø10
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Standards BS 1363-4, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Catalogue



Range



DoC



Installation

