

Product Code: CPC215

Description: 45A 3 Termination Plate With Optional Cable Outlet



General Information

Dimensions (mm)	86 (W) x 86 (H) x 24 (D)		
Plate Dimensions (mm)	86 (W) x 86 (H) x 6.5 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Screwless		
Colour	White		
Insert Colour	White		
Materials	Cover Plate: Polycarbonate	Insert & Base: Polycarbonate	
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated	
	Earth Strap: Mild Steel		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	45		
Termination Type	Screw		
Terminal Size (mm)	Ø6	Terminal Torque Value (Nm)	2.5
Terminal Capacity - Solid (mm ²)	2 x 10		
Minimum Back Box Depth (mm)	35		
Cable Restraint Supplied	Yes		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		

Standards BS 5733

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

