

Product Code: CPC651

Description: 13A Fused Connection Unit Double Pole Switched



### General Information

Dimensions (mm)	86mm (W) x 86mm (H) x 23,5mm (D)	
Plate Dimensions (mm)	86mm (W) x 86mm (H) x 6,5mm (D)	
Plate Fixing Centres - Horizontal (mm)	60,3	
Style	Screwless	
Colour	White	
Insert Colour	White	
Materials	Cover Plate & Fuse Drawer: Polycarbonate	Insert, Switch & Base: Polycarbonate
	Terminals : Brass Plated Steel	Terminal Screws: Steel & Yellow Passivated
	Contacts : Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass
	Earth Strap : Mild Steel	
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Fuse Fitted Type	Plug Top Cartridge Fuse	
Termination Type	Screw	
Terminal Size (mm)	Ø4	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm <sup>2</sup> )	3 x 2,5 or 2 x 4	
Switched	Yes	
Double Pole Switch	Yes	
Twin Earth Terminals	Yes	
Product Marking	Fused	
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

**Standards** BS 1363-4, BS 1362

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

