

Product Code: CPC653BK

Description: 13A Fused Connection Unit With Neon



General Information

Dimensions (mm)	86mm (W) x 86mm (H) x 23,5mm (D)	
Plate Dimensions (mm)	86mm (W) x 86mm (H) x 6,5mm (D)	
Plate Fixing Centres - Horizontal (mm)	120.6	
Style	Screwless	
Colour	Black	
Insert Colour	Black	
Materials	Cover Plate, Neon Lens & Fuse Drawer: Polycarbonate	Insert, Switch & Base: Polycarbonate
	Terminals : Brass Plated Steel	Terminal Screws: Steel & Yellow Passivated
	Internal Busbars: Formed Pressed Brass	Earth Strap : Mild Steel
	PCB: Electronic Components	Earth Strap : Mild Steel
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Fuse Fitted Type	Plug Top Cartridge Fuse	
Termination Type	Screw	
Terminal Size (mm)	Ø4	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm ²)	3 x 2,5 or 2 x 4	
Switched	No	
Twin Earth Terminals	Yes	
Neon Indicator	Yes (Red)	Indicator Colour Red
Product Marking	Fused	
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Standards BS 1363-4, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

