

Product Code: CPC771

Description: 13A 1 Gang Switched UK Socket With USB Outlet



**General Information**

Dimensions (mm)	86mm (W) x 86mm (H) x 38,5mm (D)	
Plate Dimensions (mm)	86mm (W) x 86mm (H) x 6,5mm (D)	
Plate Fixing Centres - Horizontal (mm)	60,3	
Style	Screwless	
Colour	White	
Insert Colour	White	
Materials	Cover Plate: Polycarbonate	Insert, Switch & Base: Polycarbonate
	Terminals : Brass	Terminal Screws: Steel & Yellow Passivated
	Contacts : Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass
	PCB: Electronic Components	Earth Strap : Mild Steel
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
USB Output Type	A	
USB Number Of Outputs	1	USB Charging Total Load (A) 2.1
USB Charging Voltage (V DC)	5	USB Standby Current (mA) 2
Termination Type	Screw	
Terminal Size (mm)	Ø4	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm <sup>2</sup> )	3 x 2,5 or 2 x 4	
Number Of Socket Outlets	1	
Single Pole Switched	Yes	
Twin Earth Terminals	Yes	
Product Marking	USB 5V 2.1A	
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	Warranty - Electronics (Years) 2

**Standards** BS 1363-2: 2016 +A1: 2018, BS EN 62368-1: 2014,, BS EN 62680-1-1: 2015

**Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

