

Product Code: CPC801BK

Description: 10AX Single Pole 1 Gang 1 Way Plate Switch



General Information

Dimensions (mm)	86 (W) x 86 (H) x 31.5 (D)	
Plate Dimensions (mm)	86 (W) x 86 (H) x 6.5 (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Style	Screwless	
Colour	Black	
Insert Colour	Black	
Materials	Cover Plate: Polycarbonate	Insert, Switch & Base: Polycarbonate
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass
Operating Voltage (AC)	250	Frequency (Hz) 50
Inductive Load Rating (AX)	10	
Termination Type	Screw	
Terminal Size (mm)	Ø3	Terminal Torque Value (Nm) 0.4
Terminal Capacity - Solid (mm ²)	2 x 1.5 or 1 x 2.5	
1 Way Switch	Yes	
Single Pole Switched	Yes	
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



CLICK OR SCAN

Catalogue



Range



DoC



Installation



CLICK OR SCAN