

Product Code: CPC803SV

Description: 10AX Single Pole 3 Gang 1 Way Plate Switch



General Information

Dimensions (mm)	86mm (W) x 86mm (H) x 31.5mm (D)		
Plate Dimensions (mm)	86mm (W) x 86mm (H) x 6.5mm (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Screwless		
Colour	Silver		
Insert Colour	Silver		
Materials	Cover Plate: Polycarbonate		
	Terminals : Brass		
	Contacts : Silver "on-lay" Copper / Brass		
Operating Voltage (AC)	250	Insert, Switch & Base: Polycarbonate	
Inductive Load Rating (AX)	10	Terminal Screws: Steel & Yellow Passivated	
Load Rating Comments	Suitable For Inductive Loads	Internal Busbars: Formed Pressed Brass	
Termination Type	Screw	Frequency (Hz)	50
Terminal Size (mm)	Ø3	Terminal Torque Value (Nm)	0.4
Terminal Capacity - Solid (mm ²)	2 x 1.5 or 1 x 2.5		
1 Way Switch	Yes		
Single Pole Switched	Yes		
Minimum Back Box Depth (mm)	35		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

