



Product Code: CPC822SV

Description: 20A Double Pole 1 Gang Plate Switch



**General Information**

Dimensions (mm)	86mm (W) x 86mm (H) x 31.5mm (D)	
Plate Dimensions (mm)	86mm (W) x 86mm (H) x 6.5mm (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Style	Screwless	
Colour	Silver	
Insert Colour	Silver	
Materials	Cover Plate: Polycarbonate	Insert, Switch & Base: Polycarbonate
	Terminals : Brass	Terminal Screws: Steel & Yellow Passivated
	Contacts : Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass
	Earth Strap : Mild Steel	
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	20	
Termination Type	Screw	
Terminal Size (mm)	Ø4.4	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm <sup>2</sup> )	3 x 2.5 or 2 x 4	
Double Pole Switch	Yes	
Twin Earth Terminals	Yes	
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

**Standards** BS EN 60669-1

**Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Catalogue



Range



DoC



Installation

