

Product Code: CPC9871

Description: 13A 1 Gang Switched Universal Socket Outlet With Single 2.1A USB Outlet



General Information

Dimensions (mm)	86 (W) x 86 (H) x 39 (D)		
Plate Dimensions (mm)	86 (W) x 86 (H) x 6.5 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Screwless		
Colour	White		
Insert Colour	White		
Materials	Cover Plate: Polycarbonate	Insert, Switch & Base: Polycarbonate	
	Terminals: Mild Steel	Terminal Screws: Mild Steel	
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass	
	PCB: Mixed Components	Earth Strap: Mild Steel	
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
USB Output Type	USB Type 'A'		
USB Number Of Outputs	1	USB Charging Total Load (A)	2.1
USB Charging Voltage (V DC)	5	USB Standby Current (mA)	2
Termination Type	Screw		
Terminal Size (mm)	Ø4	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 2 x 4		
Number Of Socket Outlets	1		
Single Pole Switched	Yes		
Twin Earth Terminals	No		
Product Marking	USB 5V 2.1A		
Minimum Back Box Depth (mm)	35		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		

Standards BS 5733 (USB), IEC 62368-1 (USB), EN 62680 (USB)

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

