

Product Code: CPCg886BK

Description: 13A 2 Gang Switched Universal Socket Outlet With Type A & C USB (4.2A) Outlets



**General Information**

Dimensions (mm)	146mm (W) x 86mm (H) x 26mm (D)		
Plate Dimensions (mm)	146mm (W) x 86mm (H) x 6.5mm (D)		
Plate Fixing Centres - Horizontal (mm)	120.6		
Style	Screwless		
Colour	Black		
Insert Colour	Black		
Materials	Cover Plate: Polycarbonate Terminals : Mild Steel Contacts : Silver "on-lay" Copper / Brass PCB: Mixed Components	Insert, Switch & Base: Polycarbonate Terminal Screws: Mild Steel Internal Busbars: Formed Pressed Brass Earth Strap : Mild Steel	
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
USB Output Type	A & C		
USB Number Of Outputs	2	USB Charging Total Load (A)	4.2
USB Charging Voltage (V DC)	5	USB Standby Current (mA)	2
Termination Type	Screw		
Terminal Size (mm)	Ø4	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm <sup>2</sup> )	3 x 2.5 or 2 x 4		
Number Of Socket Outlets	2		
Single Pole Switched	Yes		
Twin Earth Terminals	Yes		
Product Marking	DC, 5V 3A, 5V 2.4A max, 4.2A		
Minimum Back Box Depth (mm)	35		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10	Warranty - Electronics (Years)	2

**Standards** BS 5733 (USB), IEC 62368-1 (USB), EN 62680 (USB)

**Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

