

Product Code: CPCg886N

Description: 13A 2 Gang Switched Universal Socket Outlet With Type A & C USB (4.2A) Outlets * Neons



General Information

Dimensions (mm)	146 (W) x 86 (H) x 26 (D)	
Plate Dimensions (mm)	146 (W) x 86 (H) x 6,5 (D)	
Plate Fixing Centres - Horizontal (mm)	120.6	
Style	Screwless	
Colour	White	
Insert Colour	White	
Materials	Cover Plate & Neon Lens: Polycarbonate Terminals: Mild Steel Contacts: Silver "on-lay" Copper / Brass PCB: Mixed Components	Insert, Switch & Base: Polycarbonate Terminal Screws: Mild Steel Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
USB Output Type	USB Type 'A' & Type 'C'	
USB Number Of Outputs	2	USB Charging Total Load (A) 4.2
USB Charging Voltage (V DC)	5	USB Standby Current (mA) 2
Termination Type	Screw	
Terminal Size (mm)	Ø4	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 2 x 4	
Number Of Socket Outlets	2	
Single Pole Switched	Yes	
Twin Earth Terminals	Yes	
Product Marking	DC, 5V 3A, 5V 2.4A max, 4.2A	
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Standards BS 5733 (USB), IEC 62368-1 (USB), EN 62680 (USB)

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Independent Charging: 5V DC, 4.2A - USB Type A (2.4A), USB Type C (3A).
Dual Charging: 5V DC, 4.2A - USB Type A (1.2A), USB Type C (3A).

