

Description: Smart Gateway Hub

Product Code: CSP010

Technical Specification

Luckinslive 422559799







Electronics: PCB & Electronic Components

General Information

Materials Housing: Polycarbonate

Operating Voltage (DC) 1.8 - 3.3

Protocol Zigbee

Signal Transmission Frequency 400MHz

Wireless Technology WIFI 801.11 b/g/n

System Requirements Mobile Device Running IOS 8 or Higher or Android 4.1x or Higher.

Indicator Colour Green Ingress Protection IP20

Working Humidity 10%-90%RH (Non-condensing)

Operational Temperature (°C) -10 to +55

Warranty (Years) 3

Standards BS EN 60950-1, BS EN 55035, BS EN 61000-3-2, BS EN 61000-3-3, BS EN 62311

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth. Required for controlling Zigbee devices via the app and voice control

Overview of how many devices can be connected:

Hardwired Connected Devices Only: 256

· Battery Powered Devices Only (With x1 Hub): 32

· Mix of Both Battery Powered and Hardwired: 256 with a Maximum of 62 Battery Powered Devices

NOTE: If you are pairing more than 128 devices within the range, please contact technical support on +44 (0) 1827 63454

Components Supplied Smart Hub, UK Plug-in Power Adaptor, Ethernet Cable, Instruction Manual

Programming Information Once paired to the app all Zigbee devices and voice control can be added.







