

Product Code: CSP033

Luckinslive 422559786

Description: Smart Temperature & Humidity Sensor



UK PS&TI



General Information

| | | |
|------------------------------|----------------------------|--|
| Materials | Housing: Polycarbonate | Electronics: PCB & Electronic Components |
| Operating Voltage (DC) | 3 | |
| Battery Type | CR 2032 (Supplied) | |
| Battery Lifetime (Approx.) | 1 Year (Dependent On Use) | |
| Protocol | Zigbee | Signal Transmission Frequency 2.4GHz |
| Temperature Accuracy (%) | ±3 | |
| Indicator Colour | Blue | |
| Ingress Protection | IP20 | |
| Working Humidity | 0%-100%RH (Non-condensing) | |
| Operational Temperature (°C) | -10 to +50 | |
| Warranty (Years) | 3 | |

Standards BS EN 60950-1, BS EN 55035, BS EN 61000-3-2, BS EN 61000-3-3, BS EN 62311

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Control linked receivers through the ClickSmart+ app
Send activation alerts to your phone

Components Supplied Smart Temperature & Humidity Sensor, CR 2032 Battery, Reset Key, Instruction Manual

Installation Overview Suitable for ceiling or wall mounting.
Self-adhesive pad applied ready for installation.

Programming Information With hub and app setup with sensor having battery installed, using the pin supplied press the reset button for five seconds and the sensor LED will start flashing. Can be paired with hub via app.

