

Product Code: CSP042

Technical Specification

Luckinslive 422559841



Description: 2 x 100W 2 Gang Smart Switching Receiver



General Information

Materials Housing: Polycarbonate Operating Voltage (AC)

220-240

Electronics: PCB & Electronic Components

Frequency (Hz) 50/60

Load Rating (W) 100 (x2) Load Rating Comments

> Termination Type Screw Terminal Size (mm)

Terminal Torque Value (Nm) 0.2 3 X 2

Terminal Capacity - Solid (mm²) 3 × 1.5

Protocol Zigbee

Signal Transmission Frequency 2.400 to 2.484GHz

Open Air Wireless Range (M) <100 Standby Current (mA) 1 Working Current (mA) 10

Indicator Colour Blue

Minimum Back Box Depth (mm) 35 (47 Flat Plate)

Ingress Protection IP20

Working Humidity 10%-90%RH Operational Temperature (°C) -10 to +40

Warranty (Years)

Standards BS EN 60669-2-1, BS EN 55035, BS EN 61000-3-2, BS EN 61000-3-3, BS EN 62311

Additional Information

No neutral connection required

Zigbee signal mesh

Utilises standard 230V switch wiring with permanent live required Voice control via ClickSmart+ Hub using Alexa and/or Google Home

Components Supplied Switching Receiver, Mounting Bracket (DIN Rail Mountable or Screw Fixable), Instruction Manual

Installation Overview No neutral connection required.

Utilises standard on/off switches

Utilises standard switches and switch wiring

Can be multi-way switch controlled along with control via the ClickSmart+ app

Programming Information

With hub and app setup and receiver wired and powered, if not in pairing mode press the switch 'On' and 'Off' five times, the receiver LED will start flashing or the switch 'On' and 'Off' no longer operates to confirm in pairing mode. Can be paired with hub via app.



Specification is subject to change without notice. Errors & Omissions excluded.

E: sales@scolmore.com | W: scolmore.com









