

Technical Specification



Male & Female Connectors: Nylon (PA66)

Terminal Screws: Steel and Yellow

Frequency (Hz) 50

Passivated

Product Code: CT1008 Description: 230V 20A 8 Gang 4 Pole Distribution Hub



General Information

Dimensions (mm) 52 (W) x 240 (H) x 77.5 (D)

Style Metal Clad Insert Colour Blue

Materials Front Plate & Back Box: Electrophoretically

Coated Steel

Terminals: Silver Plated Brass

Dust Covers: Polycarbonate

Operating Voltage (AC) 250 Resistive Load Rating (A) 20

Ingress Protection IP20
Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS 8488, BS EN 61535, BS 5733

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation. Always refer to the circuit diagram supplied with the relevant product.

Any dangerous compatibility between different manufactures installation coupler systems is not

automatically prevented by compliance with IEC 61535.

Compatible Connectors Input Connector: Input Connector: Compatible With 3 and 4 Pole Connectors (Complete or

Female)

Output Connectors: Compatible with 3 and 4 Pole Male Connectors





