Technical Specification

Product Code: CT608

Description: 250V 20A 6 Pole 8 Way Distribution Box

Luckinslive 439203504



General Information

Dimensions (mm)	120 (W) x 320 (D) x 72 (H)		
Insert Colour	Blue		
Materials	Front Plate & Back Box: Electrophoretically Coated Steel	Male & Female Connectors: Nylon (PA66)	
	Terminals: Silver Plated Brass	Terminal Screws: Steel and Yellow Passivated	
	Dust Covers: Polycarbonate		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	20		
Rated Impulse Voltage (kV)	4		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards

IEC 61535

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation.
Always refer to the circuit diagram supplied with the relevant product.
Any dangerous compatibility between different manufactures installation coupler systems is not automatically prevented by compliance with IEC 61535.

Compatible Connectors

Input Connector: Not required. Hardwired input
Output Connectors: Compatible with 6 Pole Male Connectors (CT605M)

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN