

## **Technical Specification**

Product Code: DPBZ039BK

Description: 2A Round Pin Socket Outlet







Insert: Urea

## **General Information**

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm)

Style Rounded Profile Finish Matt Bronze Insert Colour Black

Gasket Colour Black

Materials Front Plate: Stainless Steel

Rear Housing: Nylon Terminals: Brass Internal Busbars: Formed Pressed Brass

Terminal Screws: Steel & Yellow Passivated

Earth Strap: Mild Steel

Anti Microbial Certified No Operating Voltage (AC) 250 Frequency (Hz) 50

Resistive Load Rating (A) Termination Type Screw

Terminal Size (mm) Ø5 Terminal Torque Value (Nm)

Terminal Capacity - Solid (mm<sup>2</sup>)  $3 \times 1.5$ Switched No

Twin Earth Terminals No

Minimum Back Box Depth (mm) 25

Ingress Protection IP20 Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS 546

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com









