

Technical Specification

CLICK ScolmoreGROUP

Product Code: DPBZ750BK

Description: 13A Ingot Fused Connection Unit





Insert & Housing: Urea

Internal Busbars: Formed Pressed Brass

Terminals: Brass

Terminal Torque Value (Nm)

General Information

 $\begin{array}{ccc} \textbf{Dimensions (mm)} & 91 \,(\text{W}) \times 91 \,(\text{H}) \times 25 \,(\text{D}) \\ \textbf{Plate Dimensions (mm)} & 88 \,(\text{W}) \times 88 \,(\text{H}) \times 8 \,(\text{D}) \\ \textbf{Dimensions With Gasket (mm)} & 91 \,(\text{W}) \times 91 \,(\text{H}) \times 9 \,(\text{D}) \\ \end{array}$

Plate Fixing Centres - Horizontal (mm) 60.

Style Rounded Profile Finish Matt Bronze

Insert Colour Black Gasket Colour Black

Materials Front Plate: Stainless Steel
Fuse Drawer Cover: Stainless Steel

Terminal Screws: Steel & Yellow Passivated

Earth Strap: Mild Steel

Anti Microbial Certified No
Operating Voltage (AC) 250 Frequency (Hz) 50

Resistive Load Rating (A) 13

Fuse Fitted Type Plug Top Cartridge Fuse

Termination Type Screw **Terminal Size (mm)** Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Switched No Twin Earth Terminals Yes

Product Marking Fused
Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40
Warranty (Years) 20

Standards BS 1363-4, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362

E: sales@scolmore.com | W: scolmore.com









