

Technical Specification

Product Code: DPBZ751BK

Description: 13A Ingot Double Pole Switched Fused Connection Unit





General Information

Dimensions (mm) 91 (W) x 91 (H) x 26 (D) Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm)

Style Rounded Profile Finish Matt Bronze

Insert Colour Black Gasket Colour Black

Materials Front Plate: Stainless Steel

Rear Housing: Urea Switch & Fuse Drawer Cover: Stainless Steel Terminals: Brass

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Contacts: Silver "on-lay" Copper / Brass

Terminal Torque Value (Nm)

Earth Strap: Mild Steel

Frequency (Hz) 50

Anti Microbial Certified Operating Voltage (AC) 250

Resistive Load Rating (A)

Fuse Fitted Type Plug Top Cartridge Fuse

Termination Type Screw

Terminal Size (mm) Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Switched Yes Double Pole Switch Yes

Twin Earth Terminals Yes Product Marking Fused

Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 20

Standards BS 1363-4, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal











Specification is subject to change without notice. Errors & Omissions excluded.