

Product Code: DPSC595WH

Luckinslive 438821437

Description: 13A Ingot 1 Gang Switched Socket Outlet With Twin Type C USB (4.2A) Outlets



## General Information

|                                            |                                                                                                                                         |  |  |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|--|--|
| Dimensions (mm)                            | g1 (W) x g1 (H) x 28 (D)                                                                                                                |  |  |
| Plate Dimensions (mm)                      | 88 (W) x 88 (H) x 8 (D)                                                                                                                 |  |  |
| Dimensions With Gasket (mm)                | g1 (W) x g1 (H) x g (D)                                                                                                                 |  |  |
| Plate Fixing Centres - Horizontal (mm)     | 60.3                                                                                                                                    |  |  |
| Style                                      | Rounded Profile                                                                                                                         |  |  |
| Finish                                     | Satin Chrome                                                                                                                            |  |  |
| Insert Colour                              | White                                                                                                                                   |  |  |
| Gasket Colour                              | White                                                                                                                                   |  |  |
| Materials                                  | Front Plate: Stainless Steel<br>Housing: Nylon<br>Terminals: Brass<br>Contacts: Silver "on-lay" Copper / Brass<br>PCB: Mixed Components |  |  |
| Anti Microbial Certified                   | No                                                                                                                                      |  |  |
| Operating Voltage (AC)                     | 250                                                                                                                                     |  |  |
| Resistive Load Rating (A)                  | 13                                                                                                                                      |  |  |
| USB Output Type                            | USB Type 'C'                                                                                                                            |  |  |
| USB Number Of Outputs                      | 2                                                                                                                                       |  |  |
| USB Charging Voltage (V DC)                | 5                                                                                                                                       |  |  |
| Termination Type                           | Screw                                                                                                                                   |  |  |
| Terminal Size (mm)                         | Ø5                                                                                                                                      |  |  |
| Terminal Capacity - Solid (mm²)            | 3 x 2.5 or 2 x 4                                                                                                                        |  |  |
| Single Pole Switched                       | Yes                                                                                                                                     |  |  |
| 3 Pin Safety Shuttered                     | Yes                                                                                                                                     |  |  |
| Product Marking                            | 5V DC 4.2A (SHARED)                                                                                                                     |  |  |
| Minimum Back Box Depth (mm)                | 25                                                                                                                                      |  |  |
| Ingress Protection                         | IP20                                                                                                                                    |  |  |
| Operational Temperature (°C)               | -5 to +40                                                                                                                               |  |  |
| Warranty (Years)                           | 20                                                                                                                                      |  |  |
| Standards                                  | BS 1363-2: 2016 +A1: 2018, EN IEC 62368-1, EN IEC 62368-3, EN IEC 62680-1-3, EN IEC 61000-6-1 & EN 61000-6-3                            |  |  |
| Insert: Urea                               |                                                                                                                                         |  |  |
| Switch Cover: Stainless Steel              |                                                                                                                                         |  |  |
| Terminal Screws: Steel & Yellow Passivated |                                                                                                                                         |  |  |
| Internal Busbars: Formed Pressed Brass     |                                                                                                                                         |  |  |
| Earth Strap: Mild Steel                    |                                                                                                                                         |  |  |
| Frequency (Hz)                             | 50                                                                                                                                      |  |  |
| USB Charging Total Load (A)                | 4.2                                                                                                                                     |  |  |
| USB Standby Current (W)                    | 0.1                                                                                                                                     |  |  |
| Terminal Torque Value (Nm)                 | 1.2                                                                                                                                     |  |  |
| Warranty - Electronics (Years)             | 2                                                                                                                                       |  |  |

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
 The USB circuits within this socket outlet are designed to withstand insulation resistance tests at 500V.  
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
 Independent Charging: 5V DC, 4.2A – USB Type C (3A), USB Type C (3A)  
 Intelligent chip incorporated within the USB PCB adjusts the output according to the load connected.

