define®

# Technical Specification

CLICK® Scolmore GROUP

Product Code: FPBZ504BK

Luckinslive 439633349

Description: 50A Ingot 2 Gang Double Pole Switch With 13A Double Pole Switched Socket Outlet






## General Information

| | | | |
|---|---|---|---|
| Dimensions (mm) | 146 (W) x 86 (H) x 37 (D) | | |
| Plate Dimensions (mm) | 146 (W) x 86 (H) x 1.3 (D) | | |
| Dimensions With Gasket (mm) | 146 (W) x 86 (H) x 3 (D) | | |
| Plate Fixing Centres - Horizontal (mm) | 120.6 | | |
| Style | Flat Plate | | |
| Finish | Matt Bronze | | |
| Insert Colour | Black | | |
| Gasket Colour | Transparent (Neoprene) | | |
| Materials | Front Plate: Stainless Steel | Insert & Rear Housing: Urea | |
| | Terminals: Brass | Terminal Screws: Steel & Yellow Passivated | |
| | Contacts: Silver "on-lay" Copper / Brass | Internal Busbars: Formed Pressed Brass | |
| | Earth Strap: Mild Steel | | |
| Anti Microbial Certified | No | | |
| Operating Voltage (AC) | 250 | Frequency (Hz) | 50 |
| Resistive Load Rating (A) | 50 | | |
| Termination Type | Screw | | |
| Terminal Size (mm) | Ø6 | Terminal Torque Value (Nm) | 2.5 |
| Terminal Capacity - Solid ($mm^2$) | 1 x 16 | | |
| Double Pole Switch | Yes | | |
| Twin Earth Terminals | Yes | | |
| Product Marking | Cooker | | |
| Minimum Back Box Depth (mm) | 47 | | |
| Ingress Protection | IP20 | | |
| Operational Temperature (°C) | -5 to +40 | | |
| Warranty (Years) | 20 | | |

**Standards** BS 4177

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
**T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362
**E**: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN