define®

# Technical Specification

CLICK® Scolmore GROUP

Product Code: FPBZ523BK

Luckinslive 439633527

Description: 20A Ingot Double Pole Plate Switch With Optional Flex Outlet With Neon






## General Information

| | | | |
|---|---|---|---|
| Dimensions (mm) | 86 (W) x 86 (H) x 26 (D) | | |
| Plate Dimensions (mm) | 86 (W) x 86 (H) x 1.3 (D) | | |
| Dimensions With Gasket (mm) | 86 (W) x 86 (H) x 3 (D) | | |
| Plate Fixing Centres - Horizontal (mm) | 60.3 | | |
| Style | Flat Plate | | |
| Finish | Matt Bronze | | |
| Insert Colour | Black | | |
| Gasket Colour | Transparent (Neoprene) | | |
| Materials | Front Plate: Stainless Steel | Insert & Housing: Urea | |
| | Switch Cover: Stainless Steel | Neon Lens: Polycarbonate | |
| | Terminals: Brass | Terminal Screws: Steel & Yellow Passivated | |
| | Contacts: Silver "on-lay" Copper / Brass | Internal Busbars: Formed Pressed Brass | |
| | Earth Strap: Mild Steel | | |
| Anti Microbial Certified | No | | |
| Operating Voltage (AC) | 250 | Frequency (Hz) | 50 |
| Resistive Load Rating (A) | 20 | | |
| Termination Type | Screw | | |
| Terminal Size (mm) | Ø5 | Terminal Torque Value (Nm) | 1.8 |
| Terminal Capacity - Solid ($mm^2$) | 3 x 2.5 | | |
| Double Pole Switch | Yes | | |
| Twin Earth Terminals | Yes | | |
| Neon Indicator | Yes | Indicator Colour | Red |
| Flex Outlet Available | Yes | | |
| Flex Outlet Location | Front of Plate | Flex Outlet Dimension (mm) | Ø10 |
| Minimum Back Box Depth (mm) | 35 | | |
| Ingress Protection | IP20 | | |
| Operational Temperature (°C) | -5 to +40 | | |
| Warranty (Years) | 20 | | |

**Standards** BS EN 60669-1

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
**T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362
**E**: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN