define®

Technical Specification

CLiCK® Scolmore GROUP

Product Code: FPMB159BK

Description: Twin Isolated Coaxial Outlet

Luckinslive 439634319





General Information

Dimensions (mm)	86 (W) x 86 (H) x 34 (D)
Plate Dimensions (mm)	86 (W) x 86 (H) x 1.3 (D)
Dimensions With Gasket (mm)	86 (W) x 86 (H) x 3 (D)
Plate Fixing Centres - Horizontal (mm)	60.3
Style	Flat Plate
Finish	Matt Black
Insert Colour	Black
Gasket Colour	Transparent (Neoprene)
Supplied Fixing Screw Finish	Matt Black
Materials	Front Plate: Stainless Steel Earth Plate: Mild Steel
	Insert: Urea Terminals: Brass
Anti Microbial Certified	No
Termination Type	Screw
Isolated	Yes
Isolated Comments	Enables 1 way signal, reducing signal interference
Non-Isolated	No
Shielded	No
Minimum Back Box Depth (mm)	25
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	20
Warranty - Electronics (Years)	2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN