define®

# Technical Specification

CLICK® Scolmore GROUP

Product Code: FPMB660 Luckinslive 439633488

Description: 20A Double Pole 1 Gang Plate Key Lockable Switch






## General Information

| | | | |
|---|---|---|---|
| Dimensions (mm) | 86 (W) x 86 (H) x 36 (D) | | |
| Plate Dimensions (mm) | 86 (W) x 86 (H) x 1.3 (D) | | |
| Dimensions With Gasket (mm) | 86 (W) x 86 (H) x 3 (D) | | |
| Plate Fixing Centres - Horizontal (mm) | 60.3 | | |
| Style | Flat Plate | | |
| Finish | Matt Black | | |
| Gasket Colour | Transparent (Neoprene) | | |
| Supplied Fixing Screw Finish | Matt Black | | |
| Materials | Front Plate: Stainless Steel | Insert: Urea | |
| | Earth Plate & Yoke: Mild Steel | Terminals: Brass | |
| | Terminal Screws: Steel & Yellow Passivated | GridPro Module: GM2018PW | |
| Anti Microbial Certified | No | | |
| Operating Voltage (AC) | 250 | Frequency (Hz) | 50 |
| Resistive Load Rating (A) | 20 | | |
| Termination Type | Screw | | |
| Terminal Size (mm) | Ø5 | Terminal Torque Value (Nm) | 1.2 |
| Terminal Capacity - Solid ($mm^2$) | 3 x 2.5 or 2 x 4 | | |
| Modular Rocker Switches | Yes | | |
| Double Pole Switch | Yes | | |
| Twin Earth Terminals | Yes | | |
| Product Marking | On & Off | | |
| Minimum Back Box Depth (mm) | 47 | | |
| Ingress Protection | IP20 | | |
| Operational Temperature (°C) | -5 to +40 | | |
| Warranty (Years) | 20 | | |

**Standards** BS EN 60669-1

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Two keys provided (Spare keys available: SP660)
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
**T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362
**E**: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN