essentials™

Technical Specification

Product Code: FS030MB

Description: 13A 1 Gang Floor Socket Outlet

Luckinslive 439207063



General Information

Dimensions (mm)	86 (W) x 93 (D) x 5 (H)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Finish	Matt Black		
Insert Colour	Black		
Supplied Fixing Screw Finish	Matt Black		
Materials	Plate & Lid: Stainless Steel	Insert: Urea	
	Internal Busbars: Brass	Terminals: Brass	
	Terminal Screws: Steel and Yellow Passivated	Earth Bar: Mild Steel	
Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	2
Terminal Capacity - Solid (mm^2)	3 x 2.5 or 2 x 4		
Switched	No		
Twin Earth Terminals	No		
Minimum Back Box Depth (mm)	35		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN