

Product Code: GM2218BKAB-WH

Description: 20AX Double Pole Switch With LED Module



General Information

Dimensions (mm)	24.5 (W) x 50 (H) x 23.5 (D)	
Finish	Antique Brass	
Insert Colour	Black	
Switch Finish	Antique Brass	
Materials	Body & Insert: Nylon LED Lens: Polycarbonate Terminals: Brass Contacts: Silver "on-lay" Copper / Brass	Switch: Urea Switch Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated PCB Components
Anti Microbial Certified	No	
Operating Voltage (AC)	250	Frequency (Hz) 50
Inductive Load Rating (AX)	20	
Load Rating Comments	Suitable for Fluorescent or Inductive Loads	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	
Double Pole Switch	Yes	
LED Indicator	Yes	Indicator Colour Red
Product Marking	Water Heater	
Minimum Back Box Depth (mm)	25 (35 Flat Plate)	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	
Standards	BS EN 60669-1	

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
LED Indicators are not designed to withstand insulation resistance testing at 500V. Carrying out insulation resistance testing at 500V may result in damage to the LED indicator. Please disconnect prior to insulation resistance testing.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

UK Patent: GB 2578427 , UK Design Registration: 3015621

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | F: +44 (0)1827 63362
E: sales@scolmore.com | W: scolmore.com



Catalogue



Range



DoC



Installation

