

MAGFIRE

Technical Specification



Product Code: MAGPRO-DBSS1

Luckinslive 438294527

Description: MAGPRO Addressable Fire Sounder Strobe Deep Base White



General Information

Dimensions (mm)	ø105 x 22
Colour	White RAL 9016
Materials	Housing: ABS
Strobe Colour	Red
Flash Rate	1Hz
Volume Modes	2 (Low & High)
Number of Available Tones	32
Weight (Kg)	0.12
Warranty (Years)	3

Supply & Power

Operating Voltage (V DC)	16 - 32
Maximum Consumption at Communication (µA)	470
Maximum Consumption In Activation - Tone Type 27 - High Volume Level (mA)	10 (@27V DC)
Maximum Consumption In Activation - Tone Type 27 - Low Volume Level (mA)	3 (@27V DC)
Wiring Type	Analogue Addressable (MAGPRO)

Inputs & Outputs

Sound Output @ 1m (Low) (db)	81
Sound Output @ 1m (High) (db)	88

Communication

Protocol Type	Custom (Closed)
---------------	-----------------

Environment

Ingress Protection	IP21C (with mounted detector)
Operating Temperature (°C)	-10 to +55
Relative Humidity Resistance (%)	93 (±3) (@40°C)

Compatible Products MAGPRO series of CIEs
MAGPRO series of Detectors
MAGPRO-DB

Additional Information Requires MAGPRO-DB to connect to MAGPRO loop
Requires firmware version; MAGPRO16/G V6.6.2, MAGPRO96/G V4.5.2 & MAGPRO9601 1.1.3

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuke.com | **W:** espuke.com

3 yr
WARRANTY

CLICK OR SCAN

Catalogue



DoC



CLICK OR SCAN