Technical Specification

Product Code: MM390BK

Luckinslive 439633789

Description: USB Type C Throughput Module With Fly-Lead



General Information

Dimensions (mm)	25 (W) x 50 (H) x 32.5 (D)	
Colour	Black	
Materials	Cover & Housing: Polycarbonate	Terminals: Brass
Anti Microbial Certified	No	
Operating Voltage (DC)	30	
Resistive Load Rating (A)	2	
USB Output Type	USB Type 'C'	
USB Number Of Outputs	1	
Insulation Resistance (MΩ)	100	
Dielectric Withstand Voltage (V AC)	500 (for 1 Minute)	
Flylead Cable Length (mm)	100	
Flylead Overall Length (mm)	170	
Maximum Insertion Force (lbs)	4.4	
Minimum Withdrawal Force (Kg)	0.3	
Mating Cycle Minimum Durability	5000	
Flylead Bend Radius	90°	
Minimum Back Box Depth (mm)	47	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
USB Type: C

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC CLICK OR SCAN