
Technical Specification


Product Code: MM621

Luckinslive 439633815

Description: 10A/6AX Key Card Switch Engine Module







General Information

Dimension Without Front Clips (mm)	50.5 (W) x 50.5 (H) x 32 (D)		
Overall Dimensions (mm)	56.8 (W) x 50.5 (H) x 31.9 (D)		
Materials	Cover & Housing: Polycarbonate PCB: Electronic Components	Terminals& Screws: Brass	
Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50/60
Resistive Load Rating (A)	10		
Inductive Load Rating (AX)	6		
Termination Type	Screw		
Terminal Size (mm)	0.5		
Terminal Capacity - Solid (mm^2)	2 x 2.5		
LED Indicator	Yes	Indicator Colour	White
LED Indicator Status	Only illuminates when switch is OFF		
Minimum Back Box Depth (mm)	35		
Ingress Protection	IP20		
Operational Temperature (°C)	35 Max.		
Warranty (Years)	1		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
The module is not supplied with key card , cover fascia or mounting plate.
Ensure the required fascia is ordered, see SP620 fascia range.
The module will fit in to a Euro module 50mm x 50mm aperture (311 plate)
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN