

Technical Specification

CLICK® ScolmoreGROUP

Product Code: MM9130BK

Description: 13A Universal Socket Outlet Module With Shutters





Terminal Torque Value (Nm) 1.2

General Information

Dimensions (mm) 50 (W) \times 50 (H) \times 25 (D)

Colour Black

Materials Cover & Housing: Polycarbonate Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass

Anti Microbial Certified No

Operating Voltage (AC) 250 Frequency (Hz) 50

Resistive Load Rating (A) 13
Termination Type Screw

Terminal Size (mm) Ø4

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4 Minimum Back Box Depth (mm) 25 (35 Flat Plate)

 $\begin{tabular}{ll} Ingress Protection & IP20 \\ Operational Temperature (°C) & -5 to $^+40$ \\ \end{tabular}$

Warranty (Years) 1

Minimum Back Box Depth (mm) 25 (35 Flat Plate)

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Not suitable for use in the UK as does not meet the safety requirements of the UK 'Plug and Socket Safety Regulations' or BS 1363.

Plug Compatibility: 13A British Standard Plug, 2A Round Pin Plug, 16A European Schuko Plug, 2.5A 2 Pin European Plug, US 3 Pin Plug, 10A Australian Plug & 10A Chinese 3 Pole Plug









Specification is subject to change without notice. Errors & Omissions excluded.