

## **Technical Specification**

Product Code: MM9130GY

Description: 13A Universal Socket Outlet Module With Shutters





## **General Information**

Dimensions (mm) 50 (W) x 50 (H) x 25 (D)

Colour

Materials Cover & Housing: Polycarbonate

> Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass

Anti Microbial Certified

Operating Voltage (AC) 250 Frequency (Hz) 50

Resistive Load Rating (A) 13 Termination Type Screw

> Terminal Size (mm) Ø4 Terminal Torque Value (Nm) 1.2

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4 Minimum Back Box Depth (mm) 25 (35 Flat Plate)

Ingress Protection IP20 Operational Temperature (°C) -5 to +40 Warranty (Years) 1

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth. Not suitable for use in the UK as does not meet the safety requirements of the UK 'Plug and Socket Safety Regulations' or BS 1363. Plug Compatibility: 13A British Standard Plug, 2A Round Pin Plug, 16A European Schuko Plug, 2.5A 2 Pin European Plug, US 3 Pin Plug, 10A Australian Plug & 10A Chinese 3 Pole Plug







Specification is subject to change without notice. Errors & Omissions excluded.