

Technical Specification

Product Code: MM9130WH

Description: 13A Universal Socket Outlet Module With Shutters





General Information

Dimensions (mm) 50 (W) x 50 (H) x 25 (D)

> Colour Polar White

Materials Cover & Housing: Polycarbonate Terminals: Brass

> Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass

Anti Microbial Certified

Operating Voltage (AC) 250 Frequency (Hz) 50

Terminal Torque Value (Nm) 1.2

Resistive Load Rating (A) 13

Termination Type Screw

Terminal Size (mm) Ø4

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Minimum Back Box Depth (mm) 25 (35 Flat Plate)

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Not suitable for use in the UK as does not meet the safety requirements of the UK 'Plug and Socket Safety Regulations' or BS 1363. Plug Compatibility: 13A British Standard Plug, 2A Round Pin Plug, 16A European Schuko Plug, 2.5A 2 Pin European Plug, US 3 Pin Plug, 10A Australian Plug & 10A Chinese 3 Pole Plug

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362

Specification is subject to change without notice. Errors & Omissions excluded.

E: sales@scolmore.com | W: scolmore.com





