

Product Code: OA502AG

Technical Specification

Luckinslive 397504099

Description: 2 Gang IP66 Weatherproof Unfurnished Unit





General Information

Dimensions (mm) 158 (W) x 158 (H) x 90 (D)

Accessory Fixing Centres (mm) 120.6

Colour Anthracite Grey

Gasket Colour Black

Materials Cover, Housing & Clip: Polycarbonate

Seal & Gasket: Rubber

Anti Microbial Certified No Maximum Accessory Depth (mm) 35

Back Box Knockouts - Total (mm) 8 x Ø20

Back Box Knockouts - Top (mm) 1 x Ø20 Back Box Knockouts - Sides (mm) 2 x Ø20

Back Box Knockouts - Bottom (mm) 2 x Ø20 Back Box Knockouts - Rear (mm) 1 x Ø20

Ingress Protection IP66
Operational Temperature (°C) -5 to +40
Warranty (Years) 20

Standards BS 5733, BS EN 60529

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Accepts standard two gang accessory plates.







