

Technical Specification



Product Code: OA840T

Luckinslive 422441593

Description: 2 Gang 13A DP IP66 Weatherproof Outboard Switched Socket Unit With Neon (Semi-Transparent Lid)





General Information

Dimensions (mm)	158 (W) x 158 (H) x 90 (D)			
Accessory Fixing Centres (mm)	120.6			
Colour	Anthracite Grey			
Gasket Colour	Black			
Materials	Cover, Housing & Clip: Polycarbonate		Seal & Gasket: Rubber	
	Accessory Plate & Housing: Urea		Neon Lens: Polycarbonate	
	Terminals: Brass		Terminal Screws: Steel & Yellow Passivated	
	Contacts: Silver "on-lay" Copper / Brass		Internal Busbars: Formed Pressed Brass	
	Earth Strap: Mild Steel			
Anti Microbial Certified	No			
Operating Voltage (AC)	250		Frequency (Hz)	50
Resistive Load Rating (A)	13			
Termination Type	Screw			
Terminal Size (mm)	Ø5 Terminal Torque Value (Nm)			2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4			
Double Pole Switch	Yes			
Twin Earth Terminals	Yes			
Neon Indicator	Yes		Indicator Colour	Orange
Back Box Knockouts - Total (mm)	8 x Ø20			
Back Box Knockouts - Top (mm)	1 × Ø20	Back Box Kno	ckouts - Sides (mm)	2 x Ø20
Back Box Knockouts - Bottom (mm)	2 X Ø20	Back Box Kn	ockouts - Rear (mm)	1 X Ø20
Ingress Protection	IP66			
Operational Temperature (°C)	-5 to +40			
Warranty (Years)	20			
Standards BS 1363-2, BS EN 60529				

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All grey & white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses. All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 **E:** sales@scolmore.com | **W:** scolmore.com









