AquIP66®

Technical Specification

CLICK® Scolmore GROUP

Product Code: OARCDP650AG Luckinslive 439207092

Description: 13A IP66 Weatherproof Type A Passive RCD Fused Connection Unit



General Information

Dimensions (mm)	87 (W) x 158 (H) x 90 (D)		
Accessory Fixing Centres (mm)	60.3		
Colour	Anthracite Grey		
Gasket Colour	Black		
Materials	Cover, Housing & Clip: Polycarbonate	Seal & Gasket: Rubber	
	Accessory Plate & Housing: Urea	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass	
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel	
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Breaking Capacity (A)	250 (Earth Leakage)		
Through Fault Withstand (A)	1500		
Trip Speed	Less than 40ms at 150mA Residual Current		
Fuse Fitted Type	Plug Top Cartridge Fuse		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	2
Terminal Capacity - Solid (mm^2)	3 x 2.5, 2 x 4 or 1 x 6		
Switched	No		
Twin Earth Terminals	No		
Product Marking	Fused		
Back Box Knockouts - Total (mm)	7 x Ø20		
Back Box Knockouts - Top (mm)	1 x Ø20	Back Box Knockouts - Bottom (mm)	1 x Ø20
Back Box Knockouts - Rear (mm)	1 x Ø20	Back Box Knockouts - Sides (mm)	2 x Ø20
Ingress Protection	IP66		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	5		

Standards BS 1363-4, IEC 62640, BS 7288, IEC 61000-6-1, IEC 61000-6-3

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN