


Product Code: OBKV4-W

Luckinslive 438592465

Description: 4W LED IP20 Maintained Self-Test Enable / Disable Emergency Exit Box – All 4 Legends– 5500K - White



General Information

Dimensions (mm)	195 (H) x 316 (W) x 42 (D)
Materials	Housing: Powder Coated Steel; Sign: Acrylic
Colour	White
Product Weight (Kg)	0.63
Ingress Protection	IP20
Self-Test Facility	Facility to Enable or Disable
Warranty (Years)	5

Supply & Power Information

Continuous Operating Voltage (AC) (Hz)	220-240 (50/60)
Circuit Wattage (W)	4
LED Wattage (W)	4
Input Current	45
Operation Mode	Maintained
Driver Output	260-300mA
Operating Temperature (°C)	0 to +40

Luminaire Output

Colour Temperature (K)	5500
Typical Luminous Flux (lm)	60
Beam Angle (°)	140
Colour Render Index (CRI)	≥78
Viewing Distance (M)	36
LED Lifetime (L70) (Hours)	35000

Emergency Backup Information

Self-Test Facility	Facility to Enable or Disable
Emergency Luminous Flux (lm)	60
Battery Specification	3.2V 1800mAh Lithium (LiFePO4) Battery
Minimum Duration (Hours)	3

Compatible Accessories

OBKB3218 - 3.2V 1800mAh Lithium (LiFePO4) Battery With 15cm Fly Lead
--



OVIA Limited, Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 300640
E: sales@oviaUK.com | W: oviaUK.com



CLICK OR SCAN

Catalogue



Section



DoC



Installation



CLICK OR SCAN