




General Information

Dimensions (mm)	1200 (L) x 96 (W) x 83 (D)
Materials	Base: Polycarbonate Frosted Diffuser: Polycarbonate Diffuser Fixing Clips: 304 Grade Stainless Steel
Base Finish	Light Grey
Product Weight (Kg)	1.64
Ingress Protection	IP65
Impact Rating (IK)	08
Mounting	Ceiling, Wall or Suspended
Fixing Components Supplied	Surface and Suspension Brackets
Warranty (Years)	5

Supply & Power Information

Continuous Operating Voltage (AC) (Hz)	220-240 (50)
Safety Class	I
Circuit Wattage (W)	39
LED Wattage (W)	39
Input Current (mA)	195
Inrush Current/Time	7A (378ms)
Power Factor	>0.9
Operating Temperature (°C)	-20 to +40
Critical Temperature (°C)	+90
Input Terminations	4 Pole Push Fit Terminals
Cable Input Accessories	20mm IP68 Nylon Gland Supplied

Additional Information

Switch Dim dimmable driver

Luminaire Output

Colour Temperature (K)	4000
Colour Render Index (CRI)	>80
Typical Luminous Flux (lm)	4680
Efficacy (lm/W)	120
Beam Angle (°)	105
LED Lifetime (L70) (Hours)	50000

Dimming Information

Dimmable	Yes
Dimming Format	Switch Dim
Dimming Input Termination	1 Terminal (Output to retractive switch supplied by driver)
Switch Dim Voltage	See driver for information
Switch Dim Control Format	See driver for information

