

INCEPTOR® U-LITE



Technical Specification

Product Code: OV81181EMDA

Luckinslive 434775752



Description: 34W 1800mm Linear LED Utility Luminaire With Self-Test Emergency & DALI CCT
IP65



General Information

Dimensions (mm)	1800 (L) x 96 (W) x 90 (D)
Materials	Base: Polycarbonate Frosted Diffuser: Polycarbonate Diffuser Fixing Clips: 304 Grade Stainless Steel
Base Finish	Light Grey
Product Weight (Kg)	2.45
Ingress Protection	IP65
Impact Rating (IK)	08
Mounting	Ceiling, Wall or Suspended
Fixing Components Supplied	Surface and Suspension Brackets
Warranty (Years)	5
Battery Warranty (Years)	4
On Site Warranty	1 Year Unregistered, 2 Year Registered (https://oviauk.com/on_site_warranty)

Supply & Power Information

Continuous Operating Voltage (AC) (Hz)	220-240 (50/60)
Safety Class	I
Circuit Wattage (W)	36
LED Wattage (W)	34
Input Current (mA)	180
Inrush Current	30A (350µs)
Power Factor	>0.9
Operating Temperature (°C)	0 to +40
Maximum Critical Temperature (°C)	+95
Input Terminations	4 Pole Push Fit Terminals
Cable Input Accessories	20mm IP68 Nylon Gland Supplied

Luminaire Output

Colour Temperature (K)	4000	5000	6500
Typical Luminous Flux (lm)	4080	4250	4080
Efficacy (lm/W)	113	118	113
Beam Angle (°)	120		
Colour Rendering Index (CRI)	>80		
Flicker Free	Yes		
LED Lifetime (L70) (Hours)	50000		

Dimming Information

Dimmable	Yes
Dimming Format	DALI
Dimming Input Termination	2 DALI Terminals
Analogue (1-10V) Information	See driver for information

Emergency Backup Information

Self-Test Facility	Yes
Emergency Luminous Flux (lm)	450
Battery Specification	6.4V 3000mAh LiFePo4
Minimum Duration (Hours)	3
Battery Warranty (Years)	4

Compatible Accessories

OVEMB6430LIS - 6.4V 3000mAh LiFePo4 Battery - Serial

Additional Information

DALI dimmable driver



OVIA Limited, Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom

T: +44 (0)1827 300640

E: sales@oviaUK.com | W: oviaUK.com



Catalogue



Section



DoC



Installation

