



General Information

| | |
|--------------------|---|
| Dimensions | 300mm (W) x 700mm (H) x 45mm (D) |
| Materials | Housing: Polycarbonate Support Bar: Aluminium Sign: Acrylic |
| Finish | White |
| Product Weight | 0.89Kg |
| Ingress Protection | IP20 |
| Warranty | 4 Years |

Luminaire Output

| | |
|-------------------------|--------------|
| Colour Temperature | 5500K |
| LED Lifetime (L70) | 30,000 Hours |
| Beam Angle | 100° |
| Typical Luminous Flux | 40lm |
| Emergency Luminous Flux | 30lm |
| Viewing Distance | 26 Metres |
| Legend Direction | Down |
| Legend Supplied | Double Sided |

Supply & Power

| | |
|---------------------------|------------------------------|
| Input Voltage & Frequency | 220-240V~ 50/60Hz |
| Electrical Safety | Class II (Double Insulated) |
| Input Power | 2W |
| Operation Mode | Maintained or Non-maintained |
| Ambient Temperature (Ta) | 0°C - +40°C |
| Critical Temperature | +70°C |
| Cable Entry | Rear Aperture |

Emergency Information

| | |
|-----------------------|--------------------------------------|
| Emergency Duration | 3 hours minimum |
| Charging Time | 24 Hours |
| Battery Specification | 3.6V 900mAh Ni-Cd Battery - Parallel |

Accessories & Replacement Battery

| | |
|--------------|--------------------------------------|
| OVEMB3609NCP | 3.6V 900mAh Ni-Cd Battery - Parallel |
| OVEMSP002 | Wall Bracket For Exit Signs |

