



General Information

Dimensions (mm)	5000 (L) x 10 (W) x 2.2 (D)
Product Weight (Kg)	0.09
Ingress Protection	IP20
Cutting Point (mm)	Every 26.3
Warranty (Years)	3

Supply & Power Information

Operating Voltage (DC)	24
Safety Class	III
LED Wattage (W/M)	14
Operating Temperature (°C)	-20 to +50
Input Connections	1m Prewired cables

Luminaire Output

LED Wattage (W/m)	14
Colour Temperature (K)	2700
Luminous Flux (1M) (lm)	576
Colour Temperature (K)	6500
Luminous Flux (1M) (lm)	738
Beam Angle (°)	180
Colour Rendering Index (CRI)	90
LED Lifetime (L70) (Hours)	60000

Compatible Accessories

- OCG30L - 30W 24V Constant Voltage LED Driver – Linear
- OCG60L - 60W 24V Constant Voltage LED Driver – Linear
- OCG90L - 90W 24V Constant Voltage LED Driver – Linear
- OCG250L - 250W 24V Constant Voltage LED Driver – Linear
- OCG30C - 30W 24V Constant Voltage LED Driver – Compact
- OCG60C - 60W 24V Constant Voltage LED Driver – Compact
- OCG90C - 90W 24V Constant Voltage LED Driver – Compact
- OCG120C - 120W 24V Constant Voltage LED Driver – Compact
- OCG75LD - 75W 24V Constant Voltage Triac Dimmable LED Driver Linear
- OCG150LD - 150W 24V Constant Voltage Triac Dimmable LED Driver Linear
- OX-RC2-\$ - Dual Colour CCT Remote Control – RF
- OX-WP2-\$ - Dual Colour CCT Wall Panel – RF
- OX-RF - Controller – RF
- OX-ZB - Controller – RF & Zigbee
- OX-JC310 - 3 Pin Joining Connector For 10mm IP20 COB Strip (CCT)
- OX-JL310 - 3 Pin 150mm Joining Lead For 10mm IP20 COB Strip (CCT)
- OX-MC10 - Mounting Clips For 10mm IP20 COB Strip
- OX-SL310 - 3 Pin 2m Starter Lead For 10mm IP20 COB Strip (CCT)
- OX-SE0#** - Surface Mount Aluminium Extrusion Opal Diffuser
- OX-SE1#** - Surface Mount Wide Aluminium Extrusion Opal Diffuser
- OX-SE2#*** - Surface Mount Narrow Aluminium Extrusion Opal Diffuser
- OX-CE0#** - Surface Corner Round Aluminium Extrusion Opal Diffuser
- OX-CE1#** - Surface Corner Aluminium Extrusion Opal Diffuser
- OX-RE0#** - Recessed Aluminium Extrusion Opal Diffuser
- OX-RE1#** - Recessed Wide Aluminium Extrusion Opal Diffuser
- OX-RE2#*** - Recessed Narrow Aluminium Extrusion Opal Diffuser
- OX-PE0# - Plaster-In Slim Aluminium Extrusion Opal Diffuser
- OX-PE1# - Plaster-In Aluminium Extrusion Opal Diffuser

- Length m (2 or 3)

** - Finish (Remove "***" for Aluminium or replace with "-B" for Black)

+ - Will not accept Infinity COB strip connectors inside extrusion

\$ - Colour (Replace with "B" for Black or "W" for White)



OVIA Limited, Scolmore House, Mariner, Lichfield Road Industrial Estate,
 Tamworth, Staffordshire, B79 7UL United Kingdom
 T: +44 (0)1827 300640
 E: sales@oviaUK.com | W: oviaUK.com



CLICK OR SCAN

Catalogue



Section



DoC



Installation



CLICK OR SCAN